

Barra maciça de aço inox

ESPECIFICAÇÕES TÉCNICAS

PoL.	mm				PoL.	mm				PoL.	mm			
1/8	3,17	0,062	0,068	0,079	2	50,8	15,9	17,53	20,24	5.1/2	139,71	120,2	132,73	154,2
5/32	3,97	0,097	0,107	0,12	2.1/16	52,39	16,91	18,64	21,52	5.3/4	146,06	131,4	145,07	168,53
3/16	4,76	0,149	0,154	0,178	2.1/8	53,97	17,95	19,79	22,85	6	152,4	143,4	157,93	183,48
7/32	5,55	0,189	0,209	0,242	2.3/16	55,56	19,02	20,97	24,21	6.1/4	158,76	155,2	171,39	199,12
1/4	6,35	0,25	0,027	0,32	2.1/4	57,15	20,12	22,19	25,62	6.1/2	164,11	167,9	185,38	215,36
9/32	7,14	0,314	0,346	0,4	2.5/16	58,73	21,25	23,44	27,06	6.3/4	171,46	181,1	199,91	232,25
5/16	7,93	0,39	0,43	0,49	2.3/8	60,33	22,42	24,72	28,54	7	177,81	197,7	214,99	249,77
3/8	9,53	0,56	0,62	0,71	2.7/16	61,91	23,61	26,03	30,6	7.1/4	184,16	209,7	230,62	267,93
7/16	11,11	0,76	0,84	0,97	2.1/2	63,5	24,84	27,38	31,62	7.1/2	190,51	223,8	246,8	286,72
1/2	12,7	0,99	1,1	1,27	2.5/16	66,68	27,38	30,19	34,87	7.3/4	196,85	238,9	263,5	306,12
9/16	14,28	1,26	1,39	1,6	2.3/8	60,33	22,42	24,72	28,54	8	203,2	254,6	280,77	326,12
5,8	15,87	1,55	1,71	1,98	2.7/8	73,03	32,05	36,22	41,82	8.1/4	209,55	270,7	298,59	346,9
11/16	17,46	1,88	2,07	2,39	3	76,2	35,77	39,43	45,54	8.1/2	215,9	287,4	316,97	368,24
3/4	19,05	2,24	2,46	2,85	3.1/8	79,3	38,81	42,79	49,41	8.3/4	222,25	304,6	335,88	390,22
13/16	20,63	2,62	2,89	3,34	3.1/4	82,55	41,888	46,34	53,44	9	228,6	322,1	355,35	412,84
7/8	22,22	3,04	3,35	3,87	3.3/8	85,73	45,27	49,98	57,63	9.1/4	234,95	340,3	375,37	436,09
15/16	23,81	3,49	3,85	4,44	3.1/2	85,9	48,68	53,74	61,98	9.1/2	241,3	359	395,93	459,98
1	25,4	3,97	4,38	5,06	3.5/8	92,08	52,22	57,66	66,49	9.3/4	247,65	378,1	417,05	484,51
1.1/16	26,97	4,49	4,95	5,71	3.3/4	95,25	55,88	61,69	71,15	10	254	397,8	438,71	509,67
1.1/8	28,57	5,03	5,55	6,4	3.7/8	98,43	60,67	65,88	75,96	10.1/2	266,7	438,5	483,67	561,92
1.3/16	30,16	5,6	6,18	7,14	4	101,6	63,58	70,26	80,97	11	279,4	481,2	530,83	616,71
1.1/4	31,75	6,21	6,85	7,91	4.1/8	104,78	67,62	74,65	86,1	11.1/2	292,7	526	582,58	676,82
1.5/16	33,34	6,85	7,55	8,72	4.1/4	107,95	71,78	79,24	91,39	12	304,8	572,7	631,74	733,93
1.3/8	34,92	7,51	8,29	9,57	4.3/8	111,13	76,06	83,98	96,85	13	330,2	672,6	741,42	861,35
1.7/16	36,51	8,21	9,06	10,46	4.1/2	114,3	80,47	88,84	102,46	14	355,6	779,7	858,87	998,96
1.1/2	38,1	8,94	9,86	11,39	4.5/8	117,48	85,01	93,85	108,23	15	381	894,9	987,09	1146,77
1.9/16	39,69	9,7	10,7	12,35	4.3/4	120,65	89,66	98,98	114,16	16	406,4	1017,3	1123,09	1304,77
1.5/8	41,27	10,49	11,57	13,36	4.7/8	123,83	94,44	104,27	120,25	17	431,8	1148,5	1267,87	1472,96
1.3/4	44,45	12,17	13,42	15,5	5	127	99,8	109,68	126,5	18	457,32	1287,6	1421,42	1651,35
1.7/8	47,62	13,97	15,41	17,79	5.1/4	133,36	109,5	120,94	140,5	20	508	1589,5	1754,83	2038,7